

# Index

## A

- ABR (area border router), 118
- access lists, 193, 205
- ack fields, 79
- acknowledgment packets, 71
- active state, 75
- active timer, 92
- address and wildcard-mask fields, 111
- administrative distance, 8
- advertising router, 129
- Aggregator attribute, 189
- algorithms, routing protocols, 5
- always keyword, 140
- areas, 116
  - area 0, 108
  - area border router (ABR), 118
  - area IDs, 124
    - area-id field, 112
    - assigning, 111, 112, 153
- ASBR (autonomous system boundary router), 118
- ASBR summary LSAs (type 4), 120, 135
- AS-PATH attribute, 180
- ASs (autonomous systems), 5
  - Internet Registry numbers for, 163
  - ISPs' peers, 175
  - numbers, 37, 79, 163
  - types, 158
    - unique identifiers, 158
- Atomic Aggregate attribute, 188
- authentication
  - fields, 99
  - MD5, Cisco support for, 99

- RIP-2, 94, 104
  - routing updates, 103
- autonomous system boundary router (ASBR), 118
- autonomous system numbers, 37, 79
  - acquiring, 163
- autonomous systems (see ASs)

## B

- backbone area, 108, 117
- backbone router, 117
- backup designated router (see BDR)
- bandwidth, 39
  - default values, 40
  - modification of, 114
  - path, 43
- bandwidth command, 40
- BDR (backup designated router), 125, 126
  - election, 126
- BGP dampening, 175
- BGP-4 (Border Gateway Protocol 4), 157–202
  - Aggregator attribute, 189
  - AS numbers, acquisition, 163
  - AS-PATH attribute, 180
  - Atomic Aggregate attribute, 188
  - BGP table, 167, 177
    - attributes, 177
  - configuration, 163–166
  - ebgp-multihop command, 191
  - functioning, 166–191
  - I-BGP and E-BGP, 168
  - Internet, connecting to, 194–199

We'd like to hear your suggestions for improving our indexes. Send email to [index@oreilly.com](mailto:index@oreilly.com).

BGP-4 (*continued*)  
load balancing, 191  
LOCAL-PREF attribute, 186  
MED attribute, 184  
message types, 172–173  
metrics, 167  
neighbor relationships, 168  
network statement, 174  
NEXT-HOP attribute, 182  
ORIGIN attribute, 180  
peer specification, 163  
redistribute static statement, 174  
route filtering, 192–194  
    AS-PATH, filtering by, 194  
    prefix (address/mask), filtering by, 192  
route maps, 178–180  
routing policies, 158  
routing tables, 167  
    transferring routes into, 173  
synchronization with I-BGP, 176  
troubleshooting, 200–202  
updates, attributes of, 178  
Weight attribute, 185  
Border Gateway Protocol 4 (see BGP-4)

**C**  
checksum, 79, 124  
CIDR (Classless Inter-Domain Routing), 102, 158, 160–162  
    ip classless command, 162  
    route aggregation, 162  
Cisco  
    documentation, xii  
    IOS commands, route redistribution, 208  
    MD5 support, 99  
    proprietary routing protocols, xii  
    routers, serial interface configuration, 47  
classful route lookups, 60  
    vs. classless route lookups, 103  
classful routing protocols, 42  
    vs. classless routing protocols, 101–103  
Classless Inter-Domain Routing (see CIDR)  
composite metrics, 39  
    IGRP, 44  
confederations, 176  
contiguous networks, 116

convergence, 19  
    DUAL, 69, 75–78  
    diffusing computation, 77  
    local computation, 75  
    speeding up, 22  
    IGRP, 55  
core routers, 6

**D**  
database description (DD) packet, 129  
DCs (demand circuits), 143  
DD (database description) packet, 129  
dead-interval, 125  
debug commands, 93  
debug ip ospf adjacency command, 154, 155  
debug ip ospf events command, 155  
default bandwidth and delay values, 40  
default routes, 28, 57, 140  
    creation, 58  
    multiple routes, 59  
default-information-originate keyword, 147  
delay, 39  
    default values, 40  
    path, 43  
    unit of measure, 41  
delay command, 40  
demand circuits (DCs), 143  
designated router (see DR)  
Diffusing Update Algorithm (see DUAL)  
Dijkstra's algorithm, 114  
    SPF (Shortest Path First) algorithm, 5, 108  
directly connected networks, 2  
discretionary attributes, 178  
distance command, 207  
Distance Vector algorithms (see DV algorithms)  
Distance Vector protocols (see DV protocols)  
distribute-list in command, 206  
distribute-list out command, 205  
distribution routers, 6  
DR (designated router), 125, 126  
    election, 126  
DUAL (Diffusing Update Algorithm), 69, 71–78  
    convergence, 75–78  
    diffusing computation, 77  
    local computation, 75

- hello-interval, 69
- neighbor relationship, 69
- supported protocols, 69
- topology tables, 73–75

DV (Distance Vector) algorithms, 5, 33

DV (Distance Vector) protocols, 10

- timers, 20

dynamic routing, 5

- protocols, 10

**E**

E-BGP (External-BGP), 168

- peer relationships, 170
- vs. I-BGP, 175

ebgp-multihop command, 191

EGPs (exterior gateway protocols), 6, 158

EIGRP (Enhanced Interior Gateway Routing Protocol), 63

- bandwidth on low-speed links, 92
- configuring, 64
- default routes, 88
- DUAL, 71–78
- IGRP, similarities to, 63
- incompatibility, non-Cisco routers, 64
- metrics, 67
- packets, 79–82
  - headers, 79
  - IP route updates, 80
- route summarization, 84–88
  - automatic, 84–86
  - manual, 86–88
- transport protocol, 70
- troubleshooting, 90–93
  - bug lists, 92
  - debug commands, 93
  - neighbor relationships, verification, 90
  - show logging command, 92
  - stuck-in-active, 91
- updates, 68

Enhanced Interior Gateway Routing Protocol (see EIGRP)

EXEC commands

- show interface, 3
- show ip route, 2, 4

exterior gateway protocols (EGPs), 6, 158

exterior routes, 41

external links, 171

external LSAs (type 5), 120, 136

external routes, 81, 118

- types 1 and 2, 120

**F**

fast switching, 19

FC (feasibility condition), 72

FD (feasible distance), 72

flat routing architectures, 6

flat routing protocols, 107

floating static routes, 204

flush timer, 20

FS (feasible successor), 72

**G**

gateway of last resort, 57

**H**

hello packets, 68

- format, 122–126

hello protocol, 122

hello-interval, 69, 125

hierarchical routing architectures, 6

hierarchical routing protocols, 107

hold-down timer, 20

hold-time, 69

- hello-interval, and (DUAL), 70

hops, maximum value, 43

**I**

IANA (Internet Assigned Numbers Authority), private addresses, 162

I-BGP (Internal-BGP), 168

- mesh, 176
- peer relationships, 170
- synchronization, 176
- vs. E-BGP, 175

IGPs (interior gateway protocols), 5, 158

- BGP, load balancing of, 191

IGRP (Interior Gateway Routing Protocol), 33–62

- AS numbers, 37
- bandwidth and delay commands, 40
- classful route lookups, 60
- composite metrics, 44
- configuring a network, 33
- default routes, 57
- hold-downs, disabling, 56
- IGRP command, 35
- metrics, 33, 38
  - customizing, 45
- parallel paths, 50

IGRP (*continued*)  
  process ID, 37  
  RIP, similarities to, 55  
  route summarization, 56  
  routing updates, 41  
  scaling, 61  
  timers, 55  
  unequal metric load balancing, 50  
  update packets, 41  
  updates  
    frequency, 54  
    processing, 49  
initialization bit, 69  
inter-area routes, 120  
interface configuration mode, RIP-1, RIP-2  
  interworking, 100  
interior gateway protocols (see IGPs)  
Interior Gateway Routing Protocol (see IGRP)  
internal links, 171  
internal router, 118  
internal routes, 41, 80  
Internet Exchanges, 159  
Internet Registries, 160  
  address portability, 162  
  AS numbers, 163  
intra-area routes, 120  
invalid timer, 20  
IOS commands, route redistribution, 208  
IP addresses, 162  
  portability, 162  
ip as-path access-list command, 194  
ip classless command, 162  
ip ospf network broadcast command, 149  
ip prefix-list command, 193  
ip route command, 4  
IP routing, xi, 1  
  underlying processes, 9  
IP routing commands, xii  
ISPs (Internet service providers)  
  choice of, 199  
  peers, ASs, 175

## K

keepalive messages, 173  
key chains, 104  
key management, 105

## L

{level-1 | level-1-2 | level-2} keywords, 209  
link reliability, 39  
link state acknowledgment packets, 130  
link state advertisements (see LSAs)  
Link State algorithm, 5, 108  
link state database, 116  
link state ID, 129  
Link State (LS) protocols, 10  
link state request packets, 130  
link utilization, 40  
load, 40  
  path, 43  
  route stability, and, 46  
load balancing, 10  
  BGP, 191  
LOCAL-PREF attribute, 186  
longest prefix match, 8, 103  
loop freedom, 72  
LS type, 129  
LSAs (link state advertisements), 119  
  ASBR summary LSAs (type 4), 135  
  external LSAs (type 5), 136  
  flooding, 137  
  headers, 129  
  network LSAs (type 2), 134  
  NSSA external LSAs (type 7), 137  
  router LSAs (type 1), 132  
  sequence numbers, 129  
  summary LSAs (type 3), 134

## M

mandatory attributes, 178  
match keywords, 209  
Maximum Transmission Unit (see MTU)  
maximum-paths command, 211  
MD5 authentication mode, RIP-2, 104  
MED attribute, 184  
metrics, 5, 14  
  EIGRP, 67  
  IGRP, 33, 38  
  OSPF, 113  
metric-type keyword, 140  
metric-value keyword, 140, 209  
MTU (Maximum Transmission Unit), 40  
  path, 43  
multi-homed networks, 159  
mutual redistribution, 208

## N

- NAPs (network access points), 159
- NBMA networks, 148–150
- neighbor command, BGP, 168
- neighbor relationships, 69, 128, 168
  - BGP, verification under, 165
  - BGP-4, 168
  - EIGRP, verification under, 90
- neighbor router ID list, 126
- network access points (NAPs), 159
- network administration
  - IOS commands, route redistribution, 208
  - multiple routing protocols, managing, 207
  - routing controls, 203–211
  - routing information, translation between domains, 208
  - steady state, 53
- network logs, 92
- network LSAs (type 2), 119, 134
- network mask, 124
- network statement, 174
- networks
  - C and R attributes, 13
  - directly connected, 2
  - IGRP, design, 57
  - internal addressing, devices, 162
  - monitoring state of, 53
  - private addresses, 162
- next hop IP addresses, 94, 99
- NEXT-HOP attribute, 182
- no auto-summary command, 174
- nontransitive attributes, 178
- no-redistribution keyword, 148
- no-summary keyword, 148
- notification message, 173
- NSSA external LSAs (type 7), 120, 137
- NSSAs (not so stubby areas), 119, 147

## O

- offset lists, 31
- offset-list command, 206
- opcode field, 79
- open message, 172
- Open Shortest Path First protocol (see OSPF)
- optional attributes, 178
- options field, 125
- ORIGIN attribute, 180

- OSPF (Open Shortest Path First) protocol, 6, 107–156
  - ABR (area border router), 118
  - administrative requirements, 156
  - ASBR (autonomous system boundary router), 118
  - backbone area, 117
  - backbone router, 117
  - configuration, 109–113
  - DCs (demand circuits), 143
  - default routes, 140
  - design, 150–153
  - Dijkstra’s algorithm, 114
  - functioning, explanation of, 121
  - hello packets, format of, 123–126
  - hello protocol, 122
  - high-speed networks, calculating costs, 114
  - interface state, 128
  - internal router, 118
  - metrics, 113
  - NBMA networks, 148–150
  - neighbor relationships, 128
  - network command, 111
  - packets, 121
  - regular area, 117
  - route summarization, 137–140
    - ABR (inter-area summarization), 138
    - ASBR (external route summarization), 139
  - route types, 120
  - show ip ospf interface command, 112, 113
  - stub areas, 145
  - topological database, 119
  - troubleshooting, 153–155
    - area IDs, 153
    - debug commands, 155
    - failure to start, 153
    - logs, 155
    - LS database, using, 155
    - overloaded routers, 154
    - route summarization, 154
    - SPF overruns, 154
    - verification of neighbor relationships, 153
  - VLs (virtual links), 141–143
- outgoing interfaces, 44

## P

- parallel paths, IGRP, 50
- passive state, 74
- passive-interface command, 204
- passwords
  - lifetimes, 105
  - routers, global configuration mode, 104
- paths, metrics, for defining, 43
- PDM (protocol-dependent module), 78
- plain-text authentication mode, RIP-2, 104
- poison reverse, 24
- private addresses, 162
- private peering, 160
- process switching, 19, 50
- process-id, 110, 209
- proprietary protocols, 108
- protocol keyword, 209
- protocol-dependent module (PDM), 78
- proxies, 162

## Q

- QCnt (queue count), 71
- queries, 71

## R

- RD (reported distance), 71
- redistribute command, 209
- redistribute static command, 174
- redistribute static statement, 174
- regular area, 117
- reliability, 39
  - path, 43
- replies, 71
- reported distance (RD), 71
- retransmission timeout (RTO), 71
- RFC 1771, 158
- RFC 1793, 143
- RFC 1918, 162
- RIP (Routing Information Protocol), 6, 10–32
  - compatibility, Versions 1 and 2, 99
  - fine tuning, 29
  - limitations, 31
  - offset lists, 31
  - RIP metric, 16
  - timers, setting, 25
  - updates, 15, 17

- RIP-2 (Routing Information Protocol Version 2), 94–106
  - authentication modes, supported, 104
  - configuration, 95–98
  - features, 94
  - packet format, 98–99
  - route summarization, 105
  - uses, 106
  - Version 1, compatibility with, 99
  - VLSM support, 95
- route lookups, classful vs. classless, 103
- route map commands, 168
- route maps, 178–180, 209
- route redistribution, 208
  - IOS commands, 208
  - potential problems, 210
- route reflectors (RRs), 176
- route summarization, 27
  - EIGRP, 84–88
  - OSPF, 137–140
  - RIP-2, 105
- route tags, 94
- route-map weight, 185
- router bgp command, 163, 168
- router dead-interval, 125
- router igrp command, 35
- router LSAs (type 1), 119, 132
- router ospf command, 110
- router priority, 125
- router rip command, 12
- routers
  - core routers, 6
  - distribution routers, 6
  - serial interface configuration, Cisco models, 47
- routing, 1
  - anomalies, 210
  - controls, administration of, 203–211
  - domains, 67
  - dynamic, 5
  - loops, 68
  - policies, 157
    - BGP, route filtering, 192–194
  - static, 3
  - updates
    - authentication, 103
    - IGRP, 41
- Routing Information Protocol (see RIP)

Routing Information Protocol Version 2  
(see RIP-2)

routing protocols  
  algorithms, 5  
  classful, 42  
    vs. classless, 101–103  
  dynamic, 10  
  features of, 6  
  flat, 107  
  hierarchical, 107  
routing tables, 7–8  
  administration, 203–211  
  BGP, size under, 167  
  BGP-4, transfer of routes, 173  
  body, 8  
  IGRP route labels, 36  
  longest prefix match, 8  
  timer values, 18, 54  
RRs (route reflectors), 176  
RTO (retransmission timeout), 71

## S

sequence fields, 79  
serial interface configuration, Cisco  
  routers, 47  
serial links and subnet masking, 95  
show interface command, 3, 39  
show ip bgp neighbor command, 171  
show ip eigrp topology command, 74  
show ip ospf database command, 155  
show ip ospf interface command, 112, 113,  
  153  
show ip route command, 2, 4, 43  
show ip route destination-network-number  
  command, 68  
show log command, 155  
SIA (stuck-in-active), 78, 91  
singly-homed networks, 159  
split horizon, 23  
SRTT (smoothed round trip time), 71  
static routing, 3  
  static routes, 3  
    floating, 204  
stub areas, 118, 145  
stub ASs, 158  
stuck-in-active (SIA), 78, 91  
subnet masks, 26  
  24- vs. 30-bit, 95  
  (see also VLSM)  
subnets keyword, 209

subnets, zero subnets, 102  
sub-subnetting, 96  
successor, 72  
summary LSAs (type 3), 120, 134  
switching modes, 19  
synchronization, 176  
system routes, 41

## T

timer values, 18  
topological address allocation, 161  
topological database, 116  
topology tables, 66, 71, 73–75  
TOS (types of service), 114  
totally stubby areas, 119, 146  
TraderMary network, 10  
transit networks, 133  
transitive attributes, 178  
troubleshooting  
  BGP, 200–202  
  EIGRP, 90–93  
  OSPF, 153–155  
type-value, 209

## U

update message, 173  
update packets, 41, 70  
update timer, 20  
updates, reliable transmission of, 69

## V

Variable Length Subnet Masks (see VLSM)  
variance command, 52  
VLs (virtual links), 141–143  
VLSM (Variable Length Subnet Masks), 26,  
  82, 102  
  EIGRP, support by, 82–84  
  OSPF, support by, 148, 150, 152  
  RIP-2, support by, 95, 102

## W

Weight attribute, 185  
weight keyword, 209  
well-known attributes, 178  
wildcard-mask, 111

## Z

zero subnets, 102

